acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/30/2017

Version number 3

Reviewed on 10/30/2017

1 Identification

Trade name: <u>245 Lead-free Alloy Solder Wire</u> Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

Application of the substance / the preparation: Flux cored solder

Details of the supplier of the safety data sheet Manufacturer/Supplier: Kester Inc. 800 West Thorndale Avenue Itasca, IL 60143 USA Tel (630) 616-4000 Tel International 00 1 630 616-4000

ITW Specialty Materials (Suzhou) Co., Ltd. Heng Qiao Road Wujiang Economic Development Zone Suzhou, Jiangsu 215200 China Tel +86 512 82060808

Kester GmbH Ganghofer Strasse 45 D-82216 Gernlinden Germany Tel +49 (0) 8142 4785 0

Information department: Product Compliance: EHS_Kester@kester.com Emergency telephone number: CHEMTREC 24-Hour Emergency Response Telephone Number : (800) 424-9300 CHEMTREC 24-Hour Emergency Response (Outside US & Canada) Telephone Number : (703) 527-3887

2 Hazard(s) identification

Classification of the substance or mixture



Skin Sens. 1 H317 May cause an allergic skin reaction.

Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms



Signal word Warning

Hazard-determining components of labeling:Modified RosinHazard statementsH317 May cause an allergic skin reaction.Precautionary statementsP261Avoid breathing dust/fume/gas/mist/vapors/sprayP280Wear protective gloves.P302+P352 If on skin: Wash with plenty of water.

(Contd. on page 2)



acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/30/2017

Version number 3

Reviewed on 10/30/2017

Trade name: 245 Lead-free Alloy Solder Wire

(Contd. of page 1) Dispose of contents/container in accordance with local/regional/national/international regulations. P501 Classification system: NFPA ratings (scale 0 - 4)

Health = 00 Fire = 0

Reactivity = 0

HMIS-ratings (scale 0 - 4)



Other hazards Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.

3 Composition/information on ingredients

Description: Mixture of the substances listed below with nonhazardous additions.

CAS No.	Description		% Range
CAS: 7440-31-5	TIN (Sn)		85-100%
Trade Secret	Modified Rosin	🚸 Skin Sens. 1, H317	3-5%
CAS: 7440-22-4	SILVER (Ag)		0-5%
CAS: 7440-36-0	ANTIMONY (Sb)		0-3%

4 First-aid measures

Description of first aid measures

General information: Follow general first aid procedures.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Seek immediate medical advice.

Information for doctor:

Most important symptoms and effects, both acute and delayed No further relevant information available. Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

Extinguishing media Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Special hazards arising from the substance or mixture In case of fire, the following can be released: Carbon monoxide (CO) Carbon dioxide (CO2) Aliphatic aldehydes

(Contd. on page 3) US



acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/30/2017

Version number 3

Reviewed on 10/30/2017

Trade name: 245 Lead-free Alloy Solder Wire

Advice for firefighters

Protective equipment: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Environmental precautions: Do not allow to enter sewers/ surface or ground water. Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Melted solder will solidify on cooling and can be scraped up. Use caution to avoid breathing fumes if a gas torch is used to cut up large pieces. Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. **Protective Action Criteria for Chemicals** PAC-1: CAS: 7440-31-5 TIN (Sn) 6 mg/m³ CAS: 7440-22-4 SILVER (Ag) 0.3 mg/m³ CAS: 7440-36-0 ANTIMONY (Sb) 1.5 mg/m³ CAS: 7440-50-8 COPPER (Cu) 3 mg/m³ PAC-2: CAS: 7440-31-5 TIN (Sn) 67 mg/m³ CAS: 7440-22-4 SILVER (Ag) 170 mg/m³ CAS: 7440-36-0 ANTIMONY (Sb) 13 mg/m³ CAS: 7440-50-8 COPPER (Cu) 33 mg/m³ PAC-3: CAS: 7440-31-5 TIN (Sn) 400 mg/m³ CAS: 7440-22-4 SILVER (Ag) 990 mg/m³ CAS: 7440-36-0 ANTIMONY (Sb) 80 mg/m³ CAS: 7440-50-8 COPPER (Cu) 200 mg/m³

7 Handling and storage

Handling:

Precautions for safe handling Prevent formation of dust. Information about protection against explosions and fires: No special measures required.

Conditions for safe storage, including any incompatibilities Storage: Requirements to be met by storerooms and receptacles: Store in a cool location. Information about storage in one common storage facility: Not required. Further information about storage conditions: Store in dry conditions. Exposure to sulfur or to high humidity will tarnish solder surface.

Specific end use(s) No further relevant information available.

(Contd. on page 4)

(Contd. of page 2)



acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/30/2017

Version number 3

Reviewed on 10/30/2017

Trade name: 245 Lead-free Alloy Solder Wire

8 Exposure controls/personal protection Additional information about design of technical systems: No further data: see item 7. **Control parameters** Components with limit values that require monitoring at the workplace: The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the remaining constituent has no known exposure limits. CAS: 7440-31-5 TIN (Sn) PEL Long-term value: 2 mg/m³ metal REL | Long-term value: 2 mg/m³ TLV Long-term value: 2 mg/m³ metal CAS: 7440-22-4 SILVER (Ag) PEL Long-term value: 0.01 mg/m³ REL Long-term value: 0.01 mg/m³ TLV Long-term value: 0.1 mg/m³ metal: dust and fume CAS: 7440-36-0 ANTIMONY (Sb) PEL Long-term value: 0.5 mg/m³ as Šb REL Long-term value: 0.5 mg/m³ as Sb TLV Long-term value: 0.5 mg/m³ as Sb CAS: 7440-22-4 SILVER (Ag) PEL 0.01 mg/m³ REL 0.01 mg/m³ TLV 0.1 mg/m³ Additional information: PEL = Permissible Exposure Limit (OSHA) TLV= Threshold Limit Value (ACGIH) OSHA= Occupational Safety and Health Administration ACGIH= American Conference of Governmental Industrial Hygienists Exposure controls Personal protective equipment: General protective and hygienic measures: The usual precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Breathing equipment: When ventilation is not sufficient to remove fumes from the breathing zone, a safety approved respirator or self-contained breathing apparatus should be worn. Not necessary if room is well-ventilated. Use suitable respiratory protective device in case of insufficient ventilation. (Contd. on page 5) US

(Contd. of page 3)



Safety Data Sheet acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/30/2017

Version number 3

Reviewed on 10/30/2017

Trade name: 245 Lead-free Alloy Solder Wire

Protection of hands:



Protective gloves

Material of gloves: Cloth gloves Nitrile rubber, NBR Natural rubber, NR Penetration time of glove material: The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection:



Safety glasses

9 Physical and chemical properties

Information on basic physical General Information Appearance: Form: Color: Odor:	and chemical properties Solid Grey Mild
pH-value:	Not applicable.
Change in condition Melting point/Melting range	Undetermined.
Boiling point/Boiling range:	
Flash point:	Not applicable.
Flammability (solid, gaseous)	: Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Vapor pressure:	Not applicable.
Density: Vapor density	Not determined. Not applicable.
Solubility in / Miscibility with Water:	Insoluble.
Solvent content: Organic solvents:	0.2 %
Solids content:	99.9 %

(Contd. on page 6)

(Contd. of page 4)



acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/30/2017

Version number 3

Reviewed on 10/30/2017

Trade name: 245 Lead-free Alloy Solder Wire

(Contd. of page 5)

10 Stability and reactivity

Reactivity No further relevant information available. Chemical stability Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications. Possibility of hazardous reactions No dangerous reactions known. Conditions to avoid No further relevant information available. Incompatible materials: Strong acids, strong oxidizers. Hazardous decomposition products: Carbon monoxide and carbon dioxide When heated to soldering temperatures, the solvents are evaporated and rosin may be thermally degraded to liberate aliphatic aldehydes and acids.

11 Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

Modified Rosin

Oral LD50 >4,000 mg/kg (Rat)

Dermal LD50 >2,500 mg/kg (rabbit)

Primary irritant effect:

on the skin: Possible local irritation by contact with flux or fumes.

on the eye:

Irritating effect. Smoke during soldering can cause eye irritation.

through inhalation:

Flux fumes during soldering may cause irritation and damage of mucous membranes and respiratory system.

Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

Carcinogenic categories

IARC (International Agency for Research on Cancer) None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

Toxicity

Aquatic toxicity: No further relevant information available.

(Contd. on page 7) US



acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/30/2017

Version number 3

Reviewed on 10/30/2017

(Contd. of page 6)

Trade name: 245 Lead-free Alloy Solder Wire

Additional ecological information: General notes: Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Danger to drinking water if even extremely small quantities leak into the ground. Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.

13 Disposal considerations

Waste treatment methods Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

14 Transport information

LINI Manushan	
	Not applicable
DOT, ADR, ADN, IMDG, IATA UN proper shipping name	Not applicable
DOT, ADR, ADN, IMDG, IATA	Natappliashla
Transport hazard class(es)	Not applicable
Transport hazaru class(es)	
DOT, ADR, ADN, IMDG, IATA	
Class	Not applicable
Packing group	
DOT, IMĎĞ, IATA	Not applicable
Special precautions for user	Not applicable.
Transport in bulk according to Annex II of MARPOL73	/78
and the IBC Code	Not applicable.
UN "Model Regulation":	Not applicable

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

All ingredients are listed on the following Government Inventories:

China: Inventory of Existing Chemical Substances in China (IECSC)

Korea: Korea Existing Chemicals List (ECL)

Europe: European Inventory of Existing Commercial Chemical Substances (EINECS)

Japan: Inventory of Existing and New Chemical Substances (ENCS)

Philippines: Philippine Inventory of Chemicals and Chemical Substances (PICCS)

USA: TSCA (Toxic Substances Control Act) TSCA Inventory of Chemical Substances

USA The following information relates to product regulation specific to the USA.

SARA (Superfund Amendments and Reauthorization Act)

Section 355 (extremely hazardous substances):

None of the ingredient is listed.

(Contd. on page 8)



acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/30/2017

Version number 3

Reviewed on 10/30/2017

Trade name: 245 Lead-free Alloy Solder Wire

3 -7-1		Section 313 (Specific toxic chemical listings):	
---------------	--	---	--

CAS: 7440-22-4 SILVER (Ag)

CAS: 7440-36-0 ANTIMONY (Sb)

CAS: 7440-50-8 COPPER (Cu)

TSCA new (21st Century Act) (Substances not listed)

California Proposition 65

Chemicals known to cause cancer:

WARNING: This product may contain a chemical in trace amounts known to the State of California to cause cancer.

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity:

WARNING: This product contains a chemical(s) known to the State of California to cause birth defects and/or other reproductive harm.

None of the ingredients is listed.

Carcinogenic categories

EPA (Environmental Protection Agency)

CAS: 7440-22-4 SILVER (Ag)

CAS: 7440-50-8 COPPER (Cu)

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

CANADA:

Workplace Hazardous Materials Identification (WHMIS):

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR) and the Safety Data Sheet (SDS) contains all of the information required by the CPR. **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



Signal word Warning

Hazard-determining components of labeling:Modified RosinHazard statementsH317 May cause an allergic skin reaction.Precautionary statementsP261Avoid breathing dust/fume/gas/mist/vapors/sprayP280Wear protective gloves.P302+P352 If on skin: Wash with plenty of water.P501Dispose of contents/container in accordance with local/regional/national/international regulations.Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained herein is based on data considered accurate and is offered solely for information, consideration and investigation. Kester extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The data on this Material Safety Data Sheet relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and

(Contd. of page 7)

D

D



acc. to OSHA HCS 29CFR1910.1200

Printing Date 10/30/2017

Version number 3

Reviewed on 10/30/2017

Trade name: 245 Lead-free Alloy Solder Wire

(Contd. of page 8) the necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Material Safety Data Sheet as a source for hazard information. Department issuing Safety Data Sheet (SDS): Product Compliance / EHS Department Contact: EHS Kester@kester.com Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organisation ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO) ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Skin Sens. 1: Skin sensitisation – Category 1 * Data compared to the previous version altered. US